



1108

Cast iron:GG25

Screw Specification:1/4-20BSW×1/2

Transmissible torque: 147Nm

Bore In Metric

Tools for tighten: Allen wrench 1/8"

Screws Quantity: 2

Screw tightening torque:5.6Nm

Product Code	Product Model	D1	D2	S	D (G7)	b	Js9	t	Weight (Kg)
CP001960	1108-9MM	38.32	36.92	22.3	9	3	±0.0125	D+1.4	0.15
CP001804	1108-10MM				10			D+1.4	0.15
CP049396	1108-11MM				11	4	±0.015	D+1.8	0.14
CP001827	1108-12MM				12			D+1.8	0.14
CP001837	1108-14MM				14	5	±0.015	D+2.3	0.14
CP001846	1108-15MM				15			D+2.3	0.13
CP001854	1108-16MM				16	6	±0.018	D+2.3	0.12
CP001857	1108-17MM				17			D+2.3	0.12
CP001863	1108-18MM				18	8	±0.018	D+2.8	0.12
CP049401	1108-19MM				19			D+2.8	0.11
CP001884	1108-20MM				20	5/16"	±0.018	D+2.8	0.11
CP001887	1108-21MM				21			D+2.8	0.11
CP001894	1108-22MM				22	3/8"	±0.018	D+2.8	0.11
CP001902	1108-24MM				24			D+3.3	0.09
CP001909	1108-25MM				25	7/16"	±0.018	D+3.3	0.08
CP001914	1108-26MM				26			D+3.3	0.08
CP001925	1108-28MM				28	1/2"	±0.018	D+1.3	0.06

Bore In Inches

Product Code	Product Model	D1	D2	S	D (G7)	b	t	Weight (Kg)	
CP001933	1108-3/8	1.5086"	1.4535"	0.878"	3/8"	1/8"	D+1/16"	0.15	
CP001943	1108-7/16				7/16"		D+1/16"	0.15	
CP001799	1108-1/2				1/2"		D+1/16"	0.15	
CP001957	1108-9/16				9/16"	3/16"	±0.018	D+3/32"	0.14
CP001940	1108-5/8				5/8"			D+3/32"	0.13
CP049395	1108-11/16				11/16"	1/4"	±0.018	D+3/32"	0.13
CP001930	1108-3/4				3/4"			D+3/32"	0.12
CP001832	1108-13/16				13/16"	1/4"	±0.018	D+1/8"	0.11
CP001950	1108-7/8				7/8"			D+1/8"	0.1
CP001841	1108-15/16				15/16"	1/4"	±0.018	D+1/8"	0.09
CP049402	1108-1				1"			D+1/8"	0.08
CP049394	1108-1-1/16				1-1/16"	5/16"	±0.018	D+1/8"	0.7