



## 1615

Cast iron:GG25

Screw Specification:3/8-16BSW×5/8

Transmissible torque: 486Nm

Bore In Metric

Tools for tighten: Allen wrench 3/16"

Screws Quantity: 2

Screw tightening torque:19.6Nm

Product Code	Product Model	D1	D2	S	D (G7)	b	Js9	t	Weight (Kg)	
CP003731	1615-12MM	57.07	53.97	38.1	12	4	±0.015	D+1.8	0.58	
CP049156	1615-14MM				14	5		D+2.3	0.57	
CP003761	1615-15MM				15			D+2.3	0.56	
CP003767	1615-16MM				16	6		D+2.3	0.55	
CP003776	1615-18MM				18			D+2.8	0.54	
CP003784	1615-19MM				19	D+2.8		0.54		
CP003800	1615-20MM				20	±0.018		D+2.8	0.53	
CP049163	1615-22MM				22			D+2.8	0.51	
CP003812	1615-24MM				24			8	D+3.3	0.4
CP003819	1615-25MM				25				D+3.3	0.47
CP003821	1615-26MM				26		10	D+3.3	0.46	
CP003824	1615-27MM				27			D+3.3	0.46	
CP003832	1615-28MM				28		D+3.3	0.42		
CP003847	1615-30MM				30		12	D+3.3	0.4	
CP003856	1615-32MM				32			D+3.3	0.39	
CP049169	1615-35MM				35		±0.021	D+3.3	0.34	
CP003874	1615-38MM				38	D+3.3		0.3		
CP003885	1615-40MM				40	D+3.3	0.26			
CP049170	1615-42MM				42	D+2.2	0.25			

### Bore In Inches

Product Code	Product Model	D1	D2	S	D (G7)	b	t	Weight (Kg)
CP072168	1615-3/8	2.247"	2.125"	1.5"	3/8"	1/8"	D+1/16"	0.60
CP003700	1615-1/2				1/2"		D+1/16"	0.60
CP003899	1615-5/8				5/8"	3/16"	D+3/32"	0.60
CP049167	1615-3/4				3/4"		D+3/32"	0.53
CP003905	1615-7/8				7/8"	1/4"	D+1/8"	0.50
CP003794	1615-1				1"		D+1/8"	0.47
CP049154	1615-1-1/8				1-1/8"	5/16"	D+1/8"	0.42
CP074586	1615-1-3/16				1-3/16"		D+1/8"	0.40
CP003718	1615-1-1/4				1-1/4"	3/8"	D+1/8"	0.40
CP003740	1615-1-3/8				1-3/8"		D+1/8"	0.35
CP003771	1615-1-7/16				1-7/16"	7/16"	D+1/8"	0.32
CP003711	1615-1-1/2				1-1/2"		D+1/8"	0.30
CP049158	1615-1-5/8				1-5/8"	D+1/8"	0.24	