



2517

Cast iron:GG25

Screw Specification:1/2-12BSW×1

Transmissible torque: 1310Nm

Bore In Metric

Tools for tighten: Allen wrench 1/4"

Screws Quantity: 2

Screw tightening torque:48Nm

Product Code	Product Model	D1	D2	S	D (G7)	b	Js9	t	Weight (Kg)	
CP006656	2517-10MM	85.65	82.55	44.5	10	3	±0.0125	D+1.4	1.63	
CP006715	2517-11MM				11	4		±0.015	D+1.8	1.63
CP006719	2517-12MM				12				D+1.8	1.61
CP072769	2517-14MM				14	5			D+2.3	1.6
CP006783	2517-15MM				15				D+2.3	1.6
CP048757	2517-16MM				16	6			D+2.3	1.6
CP006812	2517-17MM				17				D+2.3	1.58
CP006819	2517-18MM				18				D+2.8	1.58
CP006830	2517-19MM				19	8			D+2.8	1.56
CP006858	2517-20MM				20				D+2.8	1.54
CP006894	2517-22MM				22		D+2.8		1.52	
CP006914	2517-24MM				24		±0.018	D+3.3	1.5	
CP006927	2517-25MM				25	D+3.3		1.5		
CP006946	2517-28MM				28	D+3.3		1.44		
CP006973	2517-30MM				30	D+3.3		1.43		
CP006983	2517-32MM				32	10		D+3.3	1.41	
CP075571	2517-33MM				33			D+3.3	1.38	
CP006987	2517-34MM				34			D+3.3	1.36	
CP006999	2517-35MM				35	±0.021		D+3.3	1.35	
CP007004	2517-36MM				36			D+3.3	1.32	
CP007023	2517-38MM				38			D+3.3	1.26	
CP007041	2517-40MM				40		12	D+3.3	1.25	
CP007055	2517-42MM				42			D+3.3	1.25	
CP007057	2517-43MM				43			D+3.3	1.25	
CP007069	2517-45MM				45		14	D+3.8	1.17	
CP007074	2517-47MM				47			D+3.8	1.09	
CP007089	2517-48MM				48			D+3.8	1.06	
CP007101	2517-50MM				50			D+3.8	1	
CP007103	2517-52MM				52	18	D+4.3	1		
CP051323	2517-54MM				54		±0.021	D+4.3	0.94	
CP048785	2517-55MM				55			D+4.3	0.87	
CP007121	2517-56MM				56			D+4.3	0.86	
CP075081	2517-57MM				57			D+4.3	0.86	
CP007122	2517-58MM				58			D+4.3	0.85	
CP007134	2517-60MM				60			18	D+4.4	0.74
CP007137	2517-63MM	63	D+4.4	0.64						
CP007145	2517-65MM	65	D+3.3	0.6						