



## 2525

Cast iron:GG25

Screw Specification:1/2-12BSW\*1

Transmissible torque: 1310Nm

Bore In Metric

Tools for tighten: Allen wrench 1/4"

Screws Quantity: 2

Screw tightening torque:48Nm

Product Code	Product Model	D1	D2	S	D (G7)	b	Js9	t	Weight (Kg)
2525-15MM	2525-16MM	85.65	82.55	63.5	16	5	±0.015	D+2.3	2.15
CP007212	2525-18MM				18	6		D+2.8	2.1
CP007218	2525-19MM				19			D+2.8	2.1
CP007234	2525-20MM				20			D+2.8	2.1
CP007252	2525-22MM				22			D+2.8	2.1
CP048798	2525-24MM				24	8	D+3.3	2.1	
CP007267	2525-25MM				25		D+3.3	2.07	
CP007275	2525-28MM				28		D+3.3	2.02	
CP007291	2525-30MM				30		D+3.3	1.98	
CP048802	2525-32MM				32	10	D+3.3	1.95	
CP007303	2525-35MM				35		D+3.3	1.85	
CP048803	2525-38MM				38		D+3.3	1.79	
CP048804	2525-40MM				40		D+3.3	1.72	
CP007326	2525-42MM				42	12	D+3.3	1.67	
CP007332	2525-45MM				45		D+3.8	1.56	
CP007340	2525-48MM				48		±0.021	D+3.8	1.48
CP007346	2525-50MM				50			D+3.8	1.4
CP007352	2525-55MM				55	D+4.3		1.21	
CP007358	2525-60MM				60	D+4.4		1	
CP007359	2525-65MM				65	18	D+2.8	0.83	

Bore In Inches

Product Code	Product Model	D1	D2	S	D (G7)	b	t	Weight (Kg)
CP007365	2525-7-8	3.372"	3.25"	2.5"	7/8"	1/4"	D+1/8"	2.14
CP007225	2525-1				1"		D+1/8"	2.08
CP007174	2525-1-1/8				1-1/8"	5/16"	D+1/8"	2.01
CP007169	2525-1-1/4				1-1/4"		D+1/8"	1.95
CP007194	2525-1-3/8				1-3/8"	3/8"	D+1/8"	1.86
CP007164	2525-1-1/2				1-1/2"		D+1/8"	1.78
CP007202	2525-1-5/8				1-5/8"	7/16"	D+5/32"	1.6
CP007189	2525-1-3/4				1-3/4"		D+5/32"	1.59
CP007209	2525-1-7/8				1-7/8"	1/2"	D+5/32"	1.47
CP074590	2525-1-15/16				1-15/16"		D+5/32"	1.4
CP007282	2525-2				2"		D+5/32"	1.35
CP048795	2525-2-1/8				2-1/8"		5/8"	D+7/32"
CP048794	2525-2-1/4				2-1/4"	D+7/32"		1.11
CP007257	2525-2-3/8				2-3/8"	D+7/32"		1
CP048793	2525-2-1/2				2-1/2"	D+7/32"		0.83