



3525

Cast iron:GG25

Screw Specification:1/2-12BSW*1-1/2

Transmissible torque: 5060Nm

Bore In Metric

Tools for tighten: Allen wrench 3/8"

Screws Quantity: 3

Screw tightening torque:112Nm

Product Code	Product Model	D1	D2	S	D (G7)	b	Js9	t	Weight (Kg)	
CP048234	3525-24MM	126.8	122.68	63.5	24	8	±0.018	D+3.3	4.97	
CP012133	3525-25MM				25			D+3.3	4.95	
CP012140	3525-28MM				28			D+3.3	4.86	
CP012150	3525-30MM				30			D+3.3	4.9	
CP012165	3525-32MM				32			D+3.3	4.8	
CP012181	3525-35MM				35			D+3.3	4.7	
CP012187	3525-37MM				37	D+3.3		4.69		
CP012193	3525-38MM				38	D+3.3		4.68		
CP012205	3525-40MM				±0.021	12		40	D+3.3	4.54
CP012211	3525-42MM							42	D+3.3	4.52
CP076905	3525-43MM							43	D+3.3	4.4
CP012216	3525-45MM							14	D+3.8	4.43
CP012224	3525-48MM						48		D+3.8	4.34
CP012230	3525-50MM						50		D+3.8	4.29
CP076906	3525-54MM					16	D+4.3	4.1		
CP012235	3525-55MM						55	D+4.3	4.08	
CP012236	3525-56MM						56	D+4.3	4	
CP012246	3525-60MM					18	D+4.4	3.86		
CP012255	3525-65MM						65	D+4.4	3.65	
CP012261	3525-70MM						70	D+4.9	3.42	
CP080793	3525-72MM					±0.026	20	72	D+4.9	3.3
CP012269	3525-75MM							75	D+4.9	3.16
CP012278	3525-80MM							80	D+5.4	2.86
CP012283	3525-85MM						22	D+5.4	2.57	
CP012285	3525-89MM							89	D+5.4	2.25
CP012292	3525-90MM							25	D+5.4	2.25
CP012296	3525-95MM				95	D+5.4	1.91			
CP012060	3525-100MM				100	D+4.4	1.58			