



5040

Cast iron:GG25

Screw Specification:7/8-9BSW×2-1/4

Transmissible torque: 14200Nm

Bore In Metric

Tools for tighten: Allen wrench 3/4"

Screws Quantity: 3

Screw tightening torque:271Nm

Product Code	Product Model	D1	D2	S	D (G7)	b	Js9	t	Weight (Kg)															
CP016506	5040-50MM	177.6	170.69	101.6	50	14	±0.021	D+3.8	14.9															
CP074663	5040-55MM				55	16		18	D+4.3	14.7														
CP049979	5040-60MM				60	18			D+4.4	14.55														
CP075448	5040-65MM				177.6	170.69	101.6	65	18	±0.021	D+4.4	14.3												
CP016518	5040-70MM							70	20		20	D+4.9	12.85											
CP047957	5040-75MM							75	20			D+4.9	12.42											
CP047958	5040-80MM							177.6	170.69	101.6	80	22	±0.026	D+5.4	11.9									
CP016530	5040-85MM										85	22		25	D+5.4	11.55								
CP016536	5040-90MM										90	25			D+5.4	11.06								
CP016540	5040-95MM										177.6	170.69	101.6	95	25	±0.026	D+5.4	10.48						
CP016395	5040-100MM													100	28		D+6.4	9.32						
CP016399	5040-105MM													105			28	D+6.4	9.28					
CP016405	5040-110MM													177.6	170.69	101.6	110	32	±0.031	D+6.4	8.72			
CP047948	5040-115MM																115			D+7.4	8.72			
CP016414	5040-120MM																120			D+7.4	7.37			
CP016419	5040-125MM																177.6	170.69	101.6	125	32	±0.031	D+7.4	6.71
CP016424	5040-130MM																			130			D+7.4	5.94

Bore In Inches

Product Code	Product Model	D1	D2	S	D (G7)	b	t	Weight (Kg)
CP058167	5040-2-3/4	6.992"	6.72"	4"	2-3/4"	3/4"	D+1/4"	12.8
CP016475	5040-3				3"		D+1/4"	12.32
CP016453	5040-3-1/8				7/8"	D+5/16"	11.99	
CP016448	5040-3-1/4					3-1/4"	D+5/16"	11.75
CP016465	5040-3-3/8					3-3/8"	D+5/16"	11.41
CP016443	5040-3-1/2				1"	3-1/2"	D+5/16"	11.14
CP016461	5040-3-3/4					3-3/4"	D+3/8"	10.37
CP016501	5040-4					4"	D+3/8"	9.68
CP016486	5040-4-1/4				1 1/4"	4-1/4"	D+7/16"	8.87
CP016480	5040-4-1/2					4-1/2"	D+7/16"	8.03
CP016494	5040-4-3/4					4-3/4"	D+7/16"	7.19
CP016511	5040-5					5"	D+7/16"	6.31